

## Copper Tube - Coil

### Application:

Suitable for gasfitting (LPG and Natural Gas), plumbing and drainage, as well as air conditioning and refrigeration.

### Specifications:

- Annealed soft copper
- Designed and approved to
  - AS 1571
  - AS 1432
- Chemical composition:
  - Copper: > 99.90%
  - Phosphorus: 0.015-0.040%
- Temper: O60
- Tensile Strength > 205 Mpa
- Elongation: > 40%
- Coils available in various sizes and lengths



### Available in the following sizes (ID):

- |                                   |             |
|-----------------------------------|-------------|
| • 1/8" x 15mtr                    | (CT02)      |
| • 3/16" (4.76mm) x 0.71mm x 15mtr | (CT03)      |
| • 1/4" (6.35mm) x 0.71mm x 15mtr  | (CT04)      |
| • 5/16" (7.94mm) x 0.71mm x 15mtr | (CT05)      |
| • 3/8" (9.53mm) x 0.71mm x 15mtr  | (CT06)      |
| • 1/2" (12.7mm) x 0.71mm x 15mtr  | (CT08)      |
| • 1/2" (14.69mm) x 1.02mm x 15mtr | (CT15MM)    |
| • 4mm x 10mtr                     | (CT6938)    |
| • 6mm x 10mtr                     | (CT6939)    |
| • 10mm x 0.70mm x 10mtr           | (CTB920619) |

**Where would we be without Gas?**