

Ceelon PTFE Tape

TS1414

Application:

Ceelon thread sealing tape is a high density PolyTetraFluroEthylene (PTFE) tape manufactured from PTFE resin for use with threaded fittings and pipes used in gas and liquid applications.

Chemically compatible with:

- | | | |
|---|---|---|
| <ul style="list-style-type: none">• Aliphatic solvents• Ammonia, liquid• Aromatic, solvents• Caustics, concentrated• Caustics, dilute• Chlorinated solvents• Cutting oils• Diesel fuel oil• Ethylene glycol• Fatty acids gasohol | <ul style="list-style-type: none">• Glycerine• Heating oils• Hydraulic fluids• Hydraulic oils• Hydrogen, gaseous and liquid• Inert gases, gaseous and liquid• Jet fuel• Kerosene• Ketones• LPG | <ul style="list-style-type: none">• Mineral oils• Natural Gas• Nitrogen, gaseous and liquid• Petroleum solvents• Soap, liquid• Steam• Vegetable oils• Waters |
|---|---|---|

Features:

- Acts as a thread lubricant and anti-seize
- Prevents electrolytic corrosion of threads
- Will not crack or harden on joint
- Non-toxic
- Non-flammable
- Unlimited shelf life

Specifications:

- Composition: 100% Teflon PTFE
- Colour: White
- Density, apparent: 0.8gm/cm³
- Elongation: >100%
- Temperature Range: -268°C to +260°C
- Thickness: 0.75mm
- Width: 12mm
- Length: 10mtr

